MAC INTERNATIONAL

MAC REVOLUTION ELECTRIC

Compact Electrically Heated Static Pressure Washer

- 80°C with market leading heat retention
- 170lt stainless steel insulated water tank
- Designed to run on a standard 32amp, 400v power supply
- Super-fast water reheating
- Premium quality powder coated steel cabinet









KEY SPECIFICATION
80°C Maximum Heat
10lt-15lt/min Water Flow
16kW-24kW Heating Power
150bar-200bar Pressure
Power Supply starting from 400v, 32amp

CE

MANUFACTURED IN GREAT BRITAIN

PART OF THE REVOLUTION RANGE

www.macinternational.co.uk

MAC PRESSURE WASHERS | ZERO EMISSION PRESSURE WASHER RANGE

MAC INTERNATIONAL

MAC REVOLUTION ELECTRIC



Image shows optional internal hose reel upgrade

GO GREEN
CO_2 EMISSION FREE

MAC ELECTRIC

18/24 TECHNOLOGY

MAC 21 TECH

USER FRIENDLY CONTROL SYSTEM

FEATURES

- Variable total timed shutdown
- Soft start for heating elements
- Low water protection
- Anti-spike system
- Built in hour counter
- Fully bespoke design function - Siemens PLC

SIEMENS

STANDARD FEATURES

- Low revving 1450rpm motor
- High temperature pump
- Easy access for servicing
- Double insulated stainless steel hot water tank
- Unrivalled heat performance
- Maximum temperature output 80°C
- Simple 24v controls
- Lockable powder coated steel front door
- Hinged and removable cabinet front door and lid
- Available with MAC 18/24 Technology for 32amp, 400v power supplies

CABINET FINISH

- Powder coated steel cabinet with lockable controls
- High quality matte paint finish
- Zinc phosphate steel pre-treatment for weather proofing

THE MAC REVOLUTION E1, E3.1 & E4.1 ARE DESIGNED TO RUN ON A STANDARD 32AMP POWER SUPPLY

	REVOLUTION E1	REVOLUTION E2	REVOLUTION E3	REVOLUTION E3.1	REVOLUTION E4	REVOLUTION E4.1
Water Flow	10lt per minute	10lt per minute	13lt per minute	13lt per minute	15lt per minute	15lt per minute
Pressure	150bar, 2175psi	150bar, 2175psi	150bar, 2175psi	150bar, 2175psi	200bar, 3000psi	200bar, 3000psi
Motor Specification	3kW, 4hp, 1450rpm	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	24kW	24kW	16-24kW	24kW	16-24kW
Heating Elements	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW	2 x 12kW
Volts Amps Watts	400v/32A/24kW	400v/45A/27kW	400v/45A/30kW	400v/32A/24kW	400v/45A/30kW	400v/32A/24kW
Shutdown System	Timed	Timed	Timed	Timed total stop	Timed Total Stop	Timed
Max. Temperature	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum	80°C Maximum
Water Tank Size	170lt	170lt	170lt	170lt	170lt	170lt
Weight	200kg	200kg	210kg	215kg	215kg	215kg
Dimensions (h x w x d)	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm	130 x 102 x 70cm